



Summary of our stock program seamless fittings in WP321/321H

Dimension	Tee	Conc	Ecc.	Cap	Dimension	Tee	Conc	Ecc.	Cap
1/2"	S105	•		•	3" / 1.1/4"	S105	•		
	S405	•		•	3" / 1.1/2"	S105	•	•	•
	S805	•		•	3" / 2"	S105	•	•	•
	S160	•		•	3"	S105	•		•
3/4" / 1/2"	S105	•	•		3" / 1.1/4"	S405	•	•	
3/4"	S105	•		•	3" / 1.1/2"	S405	•	•	•
3/4" / 1/2"	S405	•	•	•	3" / 2"	S405	•	•	•
3/4"	S405	•		•	3" / 2.1/2"	S405	•	•	
3/4" / 1/2"	S805	•	•		3"	S405	•		•
3/4"	S805	•		•	3" / 1.1/4"	S805	•	•	
3/4"	S160	•		•	3" / 1.1/2"	S805	•	•	•
1" / 1/2"	S105	•			3" / 2"	S805	•	•	•
1" / 3/4"	S105	•	•		3" / 2.1/2"	S805	•	•	
1"	S105	•		•	3"	S805	•		•
1" / 1/2"	S405	•	•	•	3"	S160	•		•
1" / 3/4"	S405	•	•	•	4" / 1.1/2"	S105	•	•	
1"	S405	•		•	4" / 2"	S105	•	•	•
1" / 1/2"	S805	•	•	•	4" / 2.1/2"	S105	•	•	•
1" / 3/4"	S805	•	•	•	4" / 3"	S105	•	•	•
1"	S805	•		•	4"	S105	•		•
1" / 1/2"	S160	•	•		4" / 1.1/2"	S405	•	•	
1" / 3/4"	S160	•	•		4" / 2"	S405	•	•	•
1"	S160	•		•	4" / 2.1/2"	S405	•	•	•
1.1/4" / 1/2"	S105	•			4" / 3"	S405	•	•	•
1.1/4" / 3/4"	S105	•			4"	S405	•		•
1.1/4" / 1"	S105	•			4" / 1.1/2"	S805	•	•	
1.1/4"	S105	•		•	4" / 2"	S805	•	•	•
1.1/4" / 1/2"	S405	•	•		4" / 2.1/2"	S805	•	•	•
1.1/4" / 3/4"	S405	•	•		4" / 3"	S805	•	•	•
1.1/4" / 1"	S405	•		•	4"	S805	•		•
1.1/4"	S405	•		•	4"	S160	•		•
1.1/4" / 1/2"	S805	•	•		5" / 2"	S405	•	•	
1.1/4" / 3/4"	S805	•	•		5" / 2.1/2"	S405	•	•	
1.1/4" / 1"	S805	•	•		5" / 3"	S405	•	•	
1.1/4"	S805	•		•	5" / 4"	S405	•	•	
1.1/2" / 1/2"	S105	•	•		5"	S405	•		•
1.1/2" / 3/4"	S105	•	•	•	5" / 4"	S805	•	•	
1.1/2" / 1"	S105	•	•	•	5"	S805	•		•
1.1/2" / 1.1/4"	S105	•	•		6" / 3"	S105	•	•	
1.1/2"	S105	•		•	6" / 4"	S105	•	•	
1.1/2" / 1/2"	S405	•	•		6"	S105	•		•
1.1/2" / 3/4"	S405	•	•	•	6" / 3"	S405	•	•	•
1.1/2" / 1"	S405	•	•	•	6" / 4"	S405	•	•	•
1.1/2" / 1.1/4"	S405	•	•		6" / 5"	S405	•	•	
1.1/2"	S405	•		•	6"	S405	•		•
1.1/2" / 1/2"	S805	•	•		6" / 3"	S805	•	•	•
1.1/2" / 3/4"	S805	•	•		6" / 4"	S805	•	•	
1.1/2" / 1"	S805	•	•		6"	S805	•		•
1.1/2" / 1.1/4"	S805	•	•		8" / 4"	S105	•	•	
1.1/2"	S805	•		•	8" / 6"	S105	•	•	
1.1/2" / 1"	S160	•	•		8"	S105	•		•
1.1/2"	S160	•		•	8" / 4"	S405	•	•	•
2" / 3/4"	S105	•	•	•	8" / 5"	S405	•	•	
2" / 1"	S105	•	•	•	8" / 6"	S405	•	•	•
2" / 1.1/4"	S105	•		•	8"	S405	•		•
2" / 1.1/2"	S105	•	•		8" / 4"	S805	•	•	
2"	S105	•		•	8" / 5"	S805	•	•	
2" / 3/4"	S405	•	•	•	8" / 6"	S805	•	•	
2" / 1"	S405	•	•	•	8"	S805	•		•
2" / 1.1/4"	S405	•	•		10" / 6"	S105	•		
2" / 1.1/2"	S405	•	•	•	10" / 8"	S105	•		
2"	S405	•		•	10"	S105	•		
2" / 3/4"	S805	•	•	•	10" / 4"	S405	•	•	
2" / 1"	S805	•	•		10" / 6"	S405	•	•	•
2" / 1.1/4"	S805	•	•		10" / 8"	S405	•	•	•
2" / 1.1/2"	S805	•	•		10"	S405	•		•
2"	S805	•		•	10" / 4"	S805	•	•	
2" / 1"	S160	•	•		10" / 6"	S805	•	•	
2" / 1.1/2"	S160	•	•		10" / 8"	S805	•	•	
2"	S160	•		•	10"	S805	•		•
2.1/2" / 1"	S105	•	•		12" / 6"	S105	•		
2.1/2" / 1.1/4"	S105	•			12" / 8"	S105	•		
2.1/2" / 1.1/2"	S105	•	•		12" / 10"	S105	•		
2.1/2" / 2"	S105	•	•	•	12"	S105	•		
2.1/2"	S105	•		•	12" / 6"	S405	•	•	•
2.1/2" / 1"	S405	•	•		12" / 8"	S405	•	•	•
2.1/2" / 1.1/4"	S405	•	•		12" / 10"	S405	•	•	•
2.1/2" / 1.1/2"	S405	•	•	•	12"	S405	•		•
2.1/2" / 2"	S405	•	•	•	12" / 6"	S805	•	•	
2.1/2"	S405	•		•	12" / 8"	S805	•	•	
2.1/2" / 1"	S805	•	•		12" / 10"	S805	•	•	
2.1/2" / 1.1/4"	S805	•	•		12"	S805	•		•
2.1/2" / 1.1/2"	S805	•	•						
2.1/2" / 2"	S805	•	•						
2.1/2"	S805	•		•					

Status: January 2023

Your contact persons in Sales:

Michael Uken +49 4222/9440-301
 Alexandra Cordes +49 4222/9440-302
 Tim Gronewold +49 4222/9440-304
 Heidje Tschleppe +49 4222/9440-307
 Sören Kanert +49 4222/9440-308